

## TKU2 / TKU3 / TKU4 / TKU5

### Surveillance contacts

make the range ideal to signal the opening of doors, windows, etc.

- **Universal application**
- **Robust construction**
- **Small dimensions**
- **Sabotage by magnet impossible**







**Universal application.** The surveillance contacts announce the opening of doors, windows, etc. They can also be used to announce the state (open / closed) of the bolts.

**Great reliability.** The microswitch is built-in in a compact and non-corrosive die-cast casing. The microswitch is protected from mechanical deteriorations by a dead stop. Sabotage of the surveillance contacts by an external magnet is impossible.

**Fast and simple to install.** The self-adhesive sheets facilitate the assembly of the surveillance contacts.

**A solution for every problem.** With the four models TKU2, TKU3, TKU4, and TKU5, practically all the problems arising from the monitoring of an opening can be solved.

## Mounting examples and dimensions

TKU2	TKU3	TKU4 / TKU5
		
		

## Technical data

Single pole changeover contact	
- Switch power rating	max. 25 W
- Current	max. 1 A
- Voltage	low voltage
Actuation pressure	max. 400 g
Overtravel, depending on type and shaft extensions	4 ... 7 mm
Ambient temperature range	- 20 ... + 50° C

## Ordering data

Type	Art. No.	Designation	Weight
TKU2	230508	Surveillance contact for surface mounting	0.020 kg
TKU3	230786	Surveillance contact for recessed mounting	0.030 kg
TKU4	230799	Surveillance contact for bolt locks	0.035 kg
TKU5	244277	Surveillance contact for bolt locks with a protective spring	0.040 kg

Siemens Building Technologies AG  
 Alte Landstr. 411  
 CH-8708 Männedorf  
 Tel. +41 1 - 922 6111  
 Fax +41 1 - 922 6450  
 www.sbt.siemens.com

© 2004 Copyright by  
 Siemens Building Technologies AG  
 Data and design subject to change without notice. Supply subject to  
 availability.